

WAB AKKU PUNCH Hydraulikstanze WAB AKKU PUNCH Hydraulic Punch Driver



Leistungstarke Akku-Hydraulikstanze mit drehbarem Hydraulikzylinder und Lithium-Ionen-Akku. Die einfache Handhabung und das geringe Gewicht von 2 kg ermöglichen ein ermüdungsfreies Arbeiten. Mit dem WAB AKKU PUNCH sind ein „auf Block fahren“ des Hydraulikzylinders und Beschädigungen der Blechlocher ausgeschlossen. Der Arbeitsprozess wird elektronisch überwacht. Nach Beendigung des Stanzvorgangs wird der WAB AKKU PUNCH automatisch abgeschaltet.

Stanzleistung (max. Blechstärken)

Bis ø 63,5 mm: 2,5 mm St-Material | 2,0 mm VA-Material
 Bis 68,0 x 68,0 mm: 2,5 mm St-Material | 1,5 mm VA-Material
 Bis 92,0 x 92,0 mm: 2,0 mm St-Material | 1,5 mm VA-Material
 Größer 92,0 x 92,0 mm bis 138,0 x 138,0 mm 2mm St-Material
 (bei Verwendung von Original WAB Blechlochern)

Lieferumfang:

- 1 WAB AKKU PUNCH Hydraulikstanze
- 1 Lithium-Ionen-Akku 18V, 3 Ah
- 1 Ladegerät
- 1 Hydraulikschraube 9,5 x 19,0 mm UNF
- 1 Hydraulikschraube 19,0 x 125,0 mm UNF
- 1 Distanzbuchse
- 1 Tube Antiverschleißpaste
- 1 HSS-Co Vorbohrer (Mehrstufenbohrer)
- je 1 Blechlocher M16 – M20 – M25 – M32 – PG16
- 1 Kunststoffkoffer

Technische Daten:

- Gewicht: 2 kg
- Stanzkraft: 63 KN
- Akku-Spannung: 18V DC
- Akku-Kapazität: 3Ah
- Akku-Ladezeit: 22 min
- Lieferung im Kunststoffkoffer mit WAB Blechlocher-Satz POWER SPLIT (Dreischneider-Spaltstempel-Blechlocher für St-Material)

Art.Nr. 020014

Ersatz-Akku

Art.Nr. 020015

Ersatz-Ladegerät

Art.Nr. 020017

AKKU PUNCH ohne Blechlocher-Satz

Art.Nr. 020018

AKKU PUNCH ohne Blechlocher-Satz, Akku und Ladegerät

Art.Nr. 020019

High-capacity Akku Hydraulic Punch Driver including lithium-ion battery. Hydraulic cylinder rotates for maximum flexibility. Easy handling and low weight of 2kg enable fatigue-free punching. When using WAB AKKU PUNCH, the hydraulic cylinder will not be bottomed out and knockout punches will not be damaged. The punching process is monitored electronically. When the punching process is complete, WAB AKKU PUNCH is switched off automatically.

Punching capacities (max. sheet thickness)

Up to ø 63,5 mm: 2,5 mm mild steel | 2,0 mm stainless steel
 Up to 68,0 x 68,0 mm : 2,5 mm mild steel | 1,5 mm stainless steel
 Up to 92,0 x 92,0 mm : 2,0 mm mild steel | 1,5 mm stainless steel

Scope of supply:

- 1 WAB AKKU PUNCH Hydraulic Punch Driver
- 1 lithium-ion battery 18 V, 3 Ah
- 1 battery charger
- 1 draw stud 9,5 x 19,0 mm (3/8" x 3/4" UNF)
- 1 draw stud 19,0 x 125,0 mm (3/4" x 125,0 mm UNF)
- 1 spacer
- 1 tube lubricant
- 1 HSS-Co Pilot Drill (Multi Step Drill)
- 1 each Knockout Punch M16 – M20 – M25 – M32 – PG16
- 1 plastic case

Technical data:

- Weight: 2 kg
- Punching capacity: 63 KN
- Battery voltage: 18 V DC
- Battery capacity: 3 Ah
- Battery charging time: 22 min
- Supplied in plastic case including WAB Knockout Punch Set POWER SPLIT (Slug Splitting Knockout Punches, three point design, for mild steel).

Art.No. 020014

Replacement battery

Art.No. 020015

Replacement battery charger

Art.No. 020017

AKKU PUNCH without Knockout Punch Set

Art.No. 020018

AKKU PUNCH without Knockout Punch Set, battery and battery charger

Art.No. 020019

Zubehör für WAB Hydraulikpumpen
finden Sie auf S. 46.
Accessories for WAP hydraulic pumps can
be found on page 46.